

						
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland						
DOP07REV3 MEDITE EXTERIOR MDF.H-2						
EN 13986:2004+A1:2015						
Not Applicable						
04						
E1						
MDF.H-2						
External use as non-structural components						
Thickness Range mm	3 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30
Internal bond (N/mm²)	0.70	0.70	0.80	0.80	0.75	0.75
Swelling in thickness %	30	18	12	10	8	7
Internal bond after boil test (N/mm²)	0.20	0.20	0.15	0.15	0.12	0.12
Reaction to fire	NPD	NPD	NPD	D-s2,d0	D-s2,d0	D-s2,d0
Release of formaldehyde	E1	E1	E1	E1	E1	E1
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm
Biological	Use classes 1,2, 3					

CE symbol

Name and address of manufacturer
DoP reference.

Reference to harmonised standard

Notified body number

Year in which the CE mark was first affixed

Formaldehyde classification

Product technical class

Intended use

Thickness range

Declared performance